




# Desulco<sup>®</sup> 9001

## Product Type

9001 is manufactured using Superior Graphite's proprietary electro-thermal purification technology. This continuous high-temperature process exposes raw materials to extremely high temperatures so that impurities, including inorganic contaminants, are evaporated. 9001 is a coarse graphitized desulfurized petroleum coke. Main uses are for basic recarburisation in the cold charge for ductile and grey iron foundries.

## Product Characteristics

- High Purity
- High Consistency
- Fast Dissolution
- Very Low Gas Content
- Low Sulfur Content
- Virtually Dust-Free



## Main Properties

Carbon	>99.7%
Ash	<0.3%
Sulfur	<0.03%
Moisture	<0.2%
Size	D50 = 2.3-2.7 mm
Real Density	<1.8 g/cc
Fe	<25 ppm
O <sub>2</sub>	<300 ppm
H <sub>2</sub>	<30 ppm
N <sub>2</sub>	<100 ppm

## General Information

Formula	Carbon
Chemical Name	Carbon
CASNr	64743-05-1
RoHS	Certified
REACH	Exempted

## Standard Packaging

25 kg bags	40 bags/pallet
50 lb bags	50 bags/pallet
Bulk Bags	1000 kg/pallet
Bulk Bags	2000 lbs/pallet

This Data Sheet is provided for informational purposes. Superior Graphite makes no express or implied representation or warranty regarding the accuracy of the information set forth in this Data Sheet or regarding any Superior Graphite product or the use thereof (including without limitation, any warranty of quality, merchantability, or fitness for a particular use or purpose), except to the extent otherwise expressly provided in Superior Graphite's Terms and Conditions of Sale. Each customer of Superior Graphite assumes all risk and liability relating to its use of Superior Graphite's products and is responsible for independently testing Superior Graphite's products prior to such customer's use thereof to determine whether such products are fit and suitable for such customer's intended use or purpose. This Data Sheet is subject to change upon written notice.